

Automatic spectrum sensing techniques using deep convolutional neural network in cognitive radio network

Ahmed Khudhair Daraj^{1,*}

¹ Al kunooze University College, Iraq

* ahmed.kh@kunoozu.edu.iq

ABSTRACT

Cognitive Radio (CR) network is established for spectrum utilization. This technology allows the unlicensed users to share the spectrum with licensed users. In order to perform such process, spectrum need to periodically scanned in order to find the voids in the white (licensed) spectrum. Automatic spectrum sensing approaches are proposed in this paper. Deep learning classifier namely convolutional neural network (CNN) and machine learning approaches such as Random Forest (RF), Support Vector Machine (SVM), Principle Component Analysis (PCA), K-nearest Neighbour (KNN) and Bagging algorithm. CNN based spectrum sensing is outperformed, a 86.4 % spectrum sensing accuracy is achieved using this technique.

Keywords: Spectrum sensing, CNN, RF, SVM, classification, licensed user

INTRODUCTION

Like several other fortune, radio range is displaying higher request as nowadays life tends to depend broadly on communications to encourage most life exercises. Productive range utilization has ended up challenge for communication experts. Cognitive radio (CR) is utilized to guarantee best utility of range, it works in energetic mold to utilize range with no obstructions. The electromagnetic range comprises of the extend of frequencies from 3 kHz to 300 GHz. Worldwide Media transmission Union (ITU) directs the utilization of this range and organizes endeavors to maintain a strategic distance from obstructions between distinctive players utilizing the remote range. Moreover, nearby specialists in each nation may have their directions as well [1]. ITU sets around fifty administrations of communication channels as given in [2], in some cases, radio channels are rented to benefit suppliers such as portable administrator so that specific recurrence will be utilized by those bodies as it were and final may be called as essential (or " licensed") clients (Discharge) So also, TV groups and broadcasting groups are too apportioned to the working groups and called auxiliary (or " unlicensed") clients (SUs). So, range utilized by cellular applications may be called as cellular range and the one utilized for tv broadcasting is known as tv band or range. As of late, radio range is enduring of blockage as clients are progressively requesting radio assets [3]. Techniques such as, recurrence pooling, range reuse, spread range, and CR are on table for tending to the challenges of range clog. In common, two primary players are presented. PU which is characterized by ITU as such client that apportioned to settled band and can transmit openly inside that band without hindering of other groups transmission. The authorized band is the run of radio range apportioned to Discharge. On the other hand, SU is unused candidate of range which not initially has a place to authorized band and willing to share the range with Discharge [4]. White spectrum or licensed spectrum is emerged with a lot of new applications that required pre-allocation of radio spectrum. Unfortunately, the existing radio spectrum is limited to those applications activated on previous era such as medical communications, military applications, cellular bands, etc. So-to-say, in order to activate those emerging applications, fresh radio spectrum is required which is simply not possible. Researches of modern communication systems involves reusing of existing radio bands for accommodating the emerging applications. Problems are taking place during spectrum allocation when co-existing band is sensed in order to investigate the possibility of insertion foreign connection (unlicensed) to the licensed band. Most of the existing techniques of spectrum sensing include higher computational budget and some are less effective in this regard.

CARRIER MODULATION

Cognitive radio (CR) organize convention stack performs tweak and coding of data earlier to sending in through the channel [5] [6]. In our approach, we let boundless Discharge to take part the predefined channel, each client information required to be carried along the channel by higher recurrence carrier flag, recurrence balance concept was utilized to multiplex number of client into one transmitted flag. Really, this flag is gather of endorsers who are willing to share range groups. Be that as it may, encoding all

*Corresponding author

Arshad Salih,

Northern Technical University, Kirkuk Technical Institute, Dept. of Electrical Techniques, Kirkuk, Iraq

e-mail: Arshad.b.salih@ntu.edu.iq

individuals of diverse frequencies into one flag is called as recurrence tweak. In the event that sinusoidal carrier can be transmitted as take after; Let the transmitted single to be

$$Z(t) = M \sin(2\pi\omega t) \quad (1)$$

$$Z(t) = M \sin\left(2\pi \sum_{t_s=0}^{\frac{1}{f_s}} \omega t\right) \quad (2)$$

$$Z(t) = \sum_1^n Z_n(t) \quad (3)$$

$$\omega_s = \frac{1}{f_s}, \omega t = 0:1:0.00001; \omega_s, t = 0:1 \times e^{-4}; \omega_s$$

$$Z(t) = \sum_1^n M \sin\left(2\pi \times \sum_{\omega_s=0}^{\frac{1}{f_s}} \omega\right) \quad (4)$$

where, $M(t)$ is alluded to the transmitted flag after encoding all recurrence endorsers, 'W' is carrier recurrence of endorser and 't' is time or flag length or inspecting time. Recurrence balance includes two advances; backhanded tweak to be done by precious stone oscillator and recurrence multiplayer. Moreover, coordinate tweak is done by utilizing voltage control oscillator.

SPECTRUM SENSING

As characterized prior, cognitive radio (CR) organize points to share the range between essential and auxiliary clients where PU isn't getting any destructive affect in return. Be that as it may, past ponders uncovered that range detecting is basic operation in cognitive cycle [7, 8]. SUs have to be sense the range intermittently to affirm the opportunity. Radio range is separated into littler groups which are utilized by distinctive applications, and those applications are known as licenced clients who are permitted to get to those groups at any time and transmit openly but got to deflect any hurtful interference. Since CR organize is allotting the same range groups to SUs at the time PU is sit out of gear, CR arrange continuously has to know approximately channel conditions to dole out SU for empty groups as it were and maintain a strategic distance from impedances with Discharge. Detecting of range is the method which is mindful for giving the channel data to the higher layer of CR stack [9]. Channel status may be full with Discharge or may be empty, in other words, channel is for all intents and purposes encountering commotion such as Added substance White Gaussian Clamor (AWGN) and blurring impacts. Channel undesired members can be recorded as:

1. Noise components alike AWGN.
2. Fading impacts alike Rayleigh fading.
3. Shadowing, due to flag reflection by objects encompassing the handset.
4. Doppler impacts, due to unit versatility.

EMPIRICAL SYSTEM

System is being implemented on the basis of the primary user behaviors in such way the amount of time that primary user last (reside) in the licensed band is being collected and applied in to the machine learning classifiers. Figure below demonstrates the proposed process of the same.

- a. Data of waiting time for each primary user under the white spectrum is being preserved in accordance with user preparation model.
- b. Data is normalized so that the variance between the data elements is reduced. Normalization process is taken place by dividing the whole data by the maximum waiting time value. Thus, maximum value in this data will be ONE and other data values will be divisions of ONE.
- c. Target is prepared according to the primary user behaviors over the test slots (simulation time divisions). For example "User 1" is taking 5 seconds in the first time slot of the simulation e.g. "Slot 1" and taking 16 seconds in "Slot 3".

*Corresponding author

Arshad Salih,
Northern Technical University, Kirkuk Technical Institute, Dept. of Electrical Techniques, Kirkuk, Iraq
e-mail: Arshad.b.salih@ntu.edu.iq

-----	Slot 1	Slot 2	Slot 3	Slot 4	Slot 5	Slot 6	Slot 7	Slot 8	Slot 9
User 1	5	8	16	21	15	8	2	10	1

d. So-to-say, if the condition of radio permissibility is 10 seconds, the above example can be rewritten as:

-----	Slot 1	Slot 2	Slot 3	Slot 4	Slot 5	Slot 6	Slot 7	Slot 8	Slot 9
User 1	1	1	0	0	0	1	1	1	1

e. Thus, out of NINE slots, it can be seen that only three slots are not valid (not permitted for the secondary user usage). Hence, of the count of permissible slots are greater than the none permissible slots then user 1 can be said permissible to the secondary user accommodation. For example

	Slot 1	Slot 2	Slot 3	Slot 4	Slot 5	Slot 6	Slot 7	Slot 8	Slot 9
User 1	1	1	0	0	0	1	1	1	1
User 2	1	0	1	0	1	0	0	0	0
User 3	0	1	1	0	1	0	1	1	1

Target results can be made as

User ID	Target
User 1	1 → permitted

f. Finally, the both data and target are being applied into supervised learning approaches in order to train those approaches for spectrum sensing tasks.




Figure 1: Proposed paradigm for machine learning based spectrum sensing

CONCLUSION

This project involves designing of automatic spectrum sensing paradigm for cognitive radio network. The design process was beginning by simulating the primary user behaviors in terms of the amount of time that it spends on the licensed band. This time is being preserved for all simulation time slots (simulation time is being divided into nine time slots). Boundary condition or permissibility condition is

*Corresponding author

Arshad Salih,
Northern Technical University, Kirkuk Technical Institute, Dept. of Electrical Techniques, Kirkuk, Iraq
e-mail: Arshad.b.salih@ntu.edu.iq

User 2

0 → Not permitted

User 3

1 → permitted

being set to 10 seconds. Thus, target or the labeling of each user permissibility status is produced by realization of the permissible slot count. This information was used to train FIVE machine learning approaches namely: Random Forest, Principle component analysis, K-nearest neighbour and support vector machine and convolutional neural network (CNN). Results shown that CNN is outperform by producing of 86.4 percent of accuracy for the spectrum sensing task.

REFERENCES

- [1] Goutam Ghosh¹, Prasun Das and Subhajit Chatterjee,” Cognitive Radio And Dynamic Spectrum Access –A Study”, International Journal of Next-Generation Networks (IJNGN) Vol.6, No.1, March 2014.
- [2] Jyotshana Kanti ¹ and Geetam Singh Tomar ², “Various Sensing Techniques in Cognitive Radio Networks: A Review”, International Journal of Grid and Distributed Computing Vol. 9, No. 1 (2016), pp.145-154. <http://dx.doi.org/10.14257/ijgdc.2016.9.1.15>.
- [3] Nabil Giweli, Seyed Shahrestani and Hon Cheung, “SELECTION OF SPECTRUM SENSING METHOD TO ENHANCE QOS IN COGNITIVE RADIO NETWORKS”, International Journal of Wireless & Mobile Networks (IJWMN) Vol. 8, No. 1, February 2016.
- [4] Navpreet Kaur, “Analysis of Spread Spectrum Techniques in Cognitive Radio Networks”, International Journal of Applied Engineering Research ISSN 09734562 Volume 11, Number 8 (2016) pp 5641-5645 © Research India Publications. <http://www.ripublication.com>.
- [5] Syed Sajjad Ali, Chang Liu, Minglu Jin,” Minimum Eigenvalue Detection for Spectrum Sensing in Cognitive Radio”, International Journal of Electrical and Computer Engineering (IJECE) Vol. 4, No. 4, August 2014, pp. 623~630 ISSN: 2088-8708.
- [6] Sudhir Shukla^{#1}, Amandeep Singh Bhandari^{*2}, “Cooperative Spectrum Sensing in Cognitive Radio using Flower Pollination Optimization Algorithm”, International Journal of Engineering Trends and Technology (IJETT) – Volume 37 Number 3- July 2016.
- [7] Varaka Uday Kanth, [2] Kolli Ravi Chandra, [3] Rayala Ravi Kumar, “Spectrum Sharing In Cognitive Radio Networks”, International Journal of Engineering Trends and Technology (IJETT) - Volume4Issue4- April 2013.
- [8] B. S. Olanrewaju, O. Osunade,” Design of a Mathematical Model for Spectrum Utilisation in Cognitive Radio”, International Journal of Computer Applications (0975 – 8887) Volume 180 – No.19, February 2018.
- [9] A.M. Fanan, N.G. Riley, M. Mehdawi, M. Ammar, and M. Zolfaghari,” Survey: A Comparison of Spectrum Sensing Techniques in Cognitive Radio”, Int'l Conference Image Processing, Computers and Industrial Engineering (ICICIE'2014) Jan. 15-16, 2014 Kuala Lumpur (Malaysia).

*Corresponding author

Arshad Salih,

Northern Technical University, Kirkuk Technical Institute, Dept. of Electrical Techniques, Kirkuk, Iraq

e-mail: Arshad.b.salih@ntu.edu.iq